

# Package: prochlmm (via r-universe)

September 4, 2024

**Title** Latent Hidden Markov Models for Response Process Data

**Version** 1.0.0

**Maintainer** Xueying Tang <xueyingtang1989@gmail.com>

**Description** Provides functions for simulating from and fitting the latent hidden Markov models for response process data (Tang, 2024) <[doi:10.1007/s11336-023-09938-1](https://doi.org/10.1007/s11336-023-09938-1)>. It also includes functions for simulating from and fitting ordinary hidden Markov models.

**BugReports** <https://github.com/xytangtang/prochlmm/issues>

**License** GPL (>= 3)

**Encoding** UTF-8

**Roxygen** list(markdown = TRUE)

**RoxygenNote** 7.3.1

**LinkingTo** Rcpp

**Imports** Rcpp (>= 1.0.8.3), statmod (>= 1.4.36)

**Repository** <https://xytangtang.r-universe.dev>

**RemoteUrl** <https://github.com/xytangtang/prochlmm>

**RemoteRef** HEAD

**RemoteSha** b7dff6b9001900a198921806d0a268761b60dd06

## Contents

compute_P1_lhmm . . . . .	2
compute_paras_hmm . . . . .	3
compute_PQ_lhmm . . . . .	4
compute_theta . . . . .	5
find_state_seq . . . . .	5
hmm . . . . .	6
lhmm . . . . .	7
prochlmm . . . . .	8
sim_hmm . . . . .	9

sim_hmm_paras . . . . .	10
sim_lhmm . . . . .	11
sim_lhmm_paras . . . . .	12

**compute\_P1\_lhmm**      *Compute LHMM probabilities from parameters*

---

## Description

Compute initial state probability from LHMM parameters; currently, the initial state probability does not depend on latent traits

## Usage

```
compute_P1_lhmm(para_P1)
```

## Arguments

para_P1	a vector of length K-1. parameters of initial state probability vector
---------	--

## Value

initial state probability vector of length K

## See Also

[compute\\_PQ\\_lhmm](#) for state-transition and state-action probabilities of LHMM, [compute\\_paras\\_hmm](#) for computing probabilities in HMM.

## Examples

```
paras <- sim_lhmm_paras(5, 2)
P1 <- compute_P1_lhmm(paras$para_P1)
```

---

compute\_paras\_hmm      *Compute probabilities from logit scale parameters in HMM*

---

## Description

Compute probabilities from logit scale parameters in HMM

## Usage

```
compute_paras_hmm(para_P, para_Q, para_P1)
```

## Arguments

para_P	K by K-1 matrix. parameters of state-transition probability matrix
para_Q	K by N-1 matrix. parameters of state-action (emission) probability matrix
para_P1	K-1 vector. parameters of initial state probability distribution

## Value

a list of three elements:

P	K by K state-transition probability matrix
Q	K by N state-action (emission) probability matrix
P1	initial state probability vector of length K

## See Also

[compute\\_PQ\\_1hmm](#), [compute\\_P1\\_1hmm](#) for computing probabilities in LHMM

## Examples

```
paras <- sim_hmm_paras(5, 2, return_prob=FALSE)
prob_paras <- compute_paras_hmm(paras$para_P, paras$para_Q, paras$para_P1)
```

**compute\_PQ\_lhmm**      *Compute LHMM probabilities from parameters*

## Description

Compute state-transition and state-action (emission) probability matrices from LHMM parameters

## Usage

```
compute_PQ_lhmm(theta, para_a, para_b, para_alpha, para_beta)
```

## Arguments

theta	latent trait
para_a	K by K-1 matrix. discrimination parameters of state transition probability matrix
para_b	K by K-1 matrix. location parameters of state transition probability matrix
para_alpha	K by N-1 matrix. discrimination parameters of state-action (emission) probability matrix
para_beta	K by N-1 matrix. location parameters of state-action (emission) probability matrix

## Value

A list of two elements

P    K by K state-transition probability matrix

Q    K by N state-action probability matrix

## See Also

[compute\\_P1\\_lhmm](#) for initial state probabilities of LHMM, [compute\\_paras\\_hmm](#) for computing probabilities in HMM.

## Examples

```
paras <- sim_lhmm_paras(5, 2)
prob_paras <- compute_PQ_lhmm(1.5, paras$para_a, paras$para_b, paras$para_alpha, paras$para_beta)
```

---

compute_theta	<i>Estimate latent traits in LHMM</i>
---------------	---------------------------------------

---

**Description**

Compute MAP estimates of latent traits given LHMM parameters

**Usage**

```
compute_theta(int_seqs, para_a, para_b, para_alpha, para_beta, para_P1, n_pts)
```

**Arguments**

int_seqs	a list of n action sequences where actions are coded as integers 0, ..., N-1
para_a	K by K-1 matrix. discrimination parameters of state transition probability matrix
para_b	K by K-1 matrix. location parameters of state transition probability matrix
para_alpha	K by N-1 matrix. discrimination parameters of state-action (emission) probability matrix
para_beta	K by N-1 matrix. location parameters of state-action (emission) probability matrix
para_P1	a vector of length K-1. parameters of initial state probability vector
n_pts	number of quadrature points

**Value**

a vector of length n. Estimated latent traits.

---

find_state_seq	<i>Viterbi algorithm for HMM</i>
----------------	----------------------------------

---

**Description**

Find the most likely hidden state sequence of an observed sequence under HMM

**Usage**

```
find_state_seq(seq, P1, P, Q)
```

**Arguments**

seq	An action sequence coded in integers
P1	initial state probability vector of length K
P	K by K state transition probability matrix
Q	K by N state-action (emission) probability matrix

**Value**

a hidden state sequence coded in integers

---

**hmm**

*MMLE of HMM*

---

**Description**

Maximum marginalized likelihood estimation of HMM. Optimization is performed through [optim](#).

**Usage**

```
hmm(action_seqs, K, paras, ...)
```

**Arguments**

- |             |  |
|-------------|--|
| action_seqs | a list of n action sequences   |
| K           | number of hidden states  |
| paras       | a list of elements named para_P1, para_P, and para_Q, providing initial values of model parameters |
| ...         | additional arguments passed to <a href="#">optim</a>   |

**Value**

a list containing the following elements

- |            |   |
|------------|---|
| seqs       | action sequences coded in integers                    |
| K          | number of hidden states                               |
| N          | number of distinct actions                            |
| paras_init | a list containing initial values of parameters        |
| paras_est  | a list containing parameter estimates                 |
| init_mllh  | initial value of the marginalized likelihood function |
| opt_mllh   | maximized marginalized likelihood function            |
| opt_res    | object returned by <a href="#">optim</a>              |

## Examples

```
# generate data
paras_true <- sim_hmm_paras(5, 2)
sim_data <- sim_hmm(20, paras_true, 4, 10)
# randomly generate initial values of parameters
paras_init <- sim_hmm_paras(5, 2, return_prob=FALSE)
# fit hmm
hmm_res <- hmm(sim_data$seqs, 2, paras_init)
```

lhmm

*MLE of LHMM*

## Description

Maximum marginalized likelihood estimation of LHMM. Marginalization over latent trait is computed numerically using Gaussian-Hermite quadratures from `statmod`. Optimization is performed through `optim`.

## Usage

```
lhmm(action_seqs, K, paras, n_pts = 500, ...)
```

## Arguments

<code>action_seqs</code>	a list of <code>n</code> action sequences
<code>K</code>	number of hidden states
<code>paras</code>	a list of elements named <code>para_a</code> , <code>para_b</code> , <code>para_alpha</code> , <code>para_beta</code> , and <code>para_P1</code> , providing initial values of model parameters
<code>n_pts</code>	number of quadrature points
<code>...</code>	additional arguments passed to <code>optim</code>

## Value

A list containing the following elements

<code>seqs</code>	action sequences coded in integers
<code>K</code>	number of hidden states
<code>N</code>	number of distinct actions
<code>paras_init</code>	a list containing initial values of parameters
<code>paras_est</code>	a list containing parameter estimates

theta_est	a vector of length n. estimated latent traits
init_mllh	initial value of the marginalized likelihood function
opt_mllh	maximized marginalized likelihood function
opt_res	object returned by <code>optim</code>

## Examples

```
# generate data
paras_true <- sim_lhmm_paras(5, 2)
sim_data <- sim_lhmm(20, paras_true, 3, 8)
# randomly initialize parameters
paras_init <- sim_lhmm_paras(5, 2)
# fit model
lhmm_res <- lhmm(sim_data$seqs, 2, paras_init)
```

## Description

This package provides functions for simulating from and fitting the latent hidden Markov models for response process data (Tang, 2024). It also includes functions for simulating from and fitting ordinary hidden Markov models.

### Data Simulation Functions

- `sim_hmm_paras` generates parameters of HMM
- `sim_hmm` generates actions sequences from HMM.
- `sim_lhmm_paras` generates parameters of LHMM
- `sim_lhmm` generates actions sequences from LHMM.

### Model Fitting Functions

- `hmm` fits HMM models. Parameters are estimated through marginalized maximum likelihood estimation.
- `lhmm` fits LHMM models. Parameters are estimated through marginalized maximum likelihood estimation.
- `compute_theta` compute MAP estimates of latent traits in LHMM.
- `find_state_seq` compute the most likely hidden state sequence.

## Acknowledgment

The development of this package is supported by National Science Foundation grant DMS-2310664.

## References

Tang, X. (2024) Latent Hidden Markov Models for Response Process Data. *Psychometrika* 89, 205-240. doi:10.1007/s11336023099381

---

sim\_hmm

*Simulating action sequences using HMM*

---

## Description

sim\_hmm generate n action sequences from HMM based on given parameters. The lengths of the generated sequences are simulated from a Poission distribution with mean mean\_len and at least min\_len.

## Usage

```
sim_hmm(n, paras, min_len, mean_len, return_state = TRUE)
```

## Arguments

n	number of action sequences to be generated
paras	a list containing specified HMM parameters: state-transition probability matrix (P), state-action probability matrix (Q), and initial state probability (P1).
min_len	minimum length of generated sequences
mean_len	mean length of generated sequences
return_state	logical. Whether generated hidden state sequences should be returned or not.

## Value

sim\_hmm returns a list of n generated action sequences if return\_state = FALSE. If return\_state = TRUE, it returns a list of two lists, seqs and state\_seqs. seqs gives the generated action sequences. state\_seqs gives the corresponding hidden state sequences.

## Examples

```
paras <- sim_hmm_paras(5,2)
sim_data <- sim_hmm(20, paras, 3, 10)
```

<code>sim_hmm_paras</code>	<i>generate HMM parameters</i>
----------------------------	--------------------------------

## Description

`sim_hmm_paras` generates logit scale parameters of HMM with K hidden states and N distinct actions from Uniform(-0.5, 0.5).

## Usage

```
sim_hmm_paras(N, K, return_prob = TRUE)
```

## Arguments

N	number of distinct actions
K	number of hidden states
return_prob	logical. indicates to return parameters in probability scale (TRUE, default) or logit scale.

## Value

a list of three elements. If `return_prob = TRUE`, the element names are P1, P, and Q. If `return_prob = FALSE`, the element names are para\_P1, para\_P, and para\_Q.

## Examples

```
# generate probability parameters
set.seed(12345)
paras1 <- sim_hmm_paras(5, 2)
names(paras1)

# generate parameters in the logit scale
set.seed(12345)
paras2 <- sim_hmm_paras(5, 2, return_prob = FALSE)
names(paras2)

paras1$P1
paras2$para_P1

# logit scale parameters can be transformed to probability parameters
all.equal(compute_paras_hmm(paras2$para_P, paras2$para_Q, paras2$para_P1), paras1)
```

---

**sim\_lhmm***Simulating action sequences using LHMM*

---

## Description

`sim_lhmm` generate n action sequences from LHMM based on given parameters. The lengths of the generated sequences are simulated from a Poission distribution with mean `mean_len` and at least `min_len`. The latent trait is generated from standard normal.

## Usage

```
sim_lhmm(n, paras, min_len, mean_len, return_state = TRUE)
```

## Arguments

<code>n</code>	number of action sequences to be generated
<code>paras</code>	a list containing specified LHMM parameters: <code>para_a</code> , <code>para_b</code> , <code>para_alpha</code> , <code>para_beta</code> , and <code>para_P1</code> .
<code>min_len</code>	minimum length of generated sequences
<code>mean_len</code>	mean length of generated sequences
<code>return_state</code>	logical. Whether generated hidden state sequences should be returned or not.

## Value

If `return_state = TRUE`, `sim_lhmm` returns a list of three elements

<code>seqs</code>	a list of n generated action sequences
<code>theta</code>	latent traits as a vector of length n
<code>state_seqs</code>	a list of n hidden state sequences

If `return_state = FALSE`, the returned list only contains `seqs` and `theta`.

## Examples

```
paras <- sim_lhmm_paras(5,2)
sim_data <- sim_lhmm(20, paras, 4, 10)
```

---

**sim\_lhmm\_paras**      *generate LHMM parameters*

---

**Description**

`sim_hmm_paras` generates the parameters of LHMM with K hidden states and N distinct actions from Uniform(-0.5, 0.5).

**Usage**

`sim_lhmm_paras(N, K)`

**Arguments**

N	number of distinct actions
K	number of hidden states

**Value**

a list of five elements, `para_a`, `para_b`, `para_alpha`, `para_beta`, and `para_P1`.

**Examples**

```
paras <- sim_lhmm_paras(5, 2)
paras
```

# Index

compute\_P1\_lhmm, 2, 3, 4  
compute\_paras\_hmm, 2, 3, 4  
compute\_PQ\_lhmm, 2, 3, 4  
compute\_theta, 5, 8  
  
find\_state\_seq, 5, 8  
  
hmm, 6, 8  
  
lhmm, 7, 8  
  
optim, 6–8  
  
proclhmm, 8  
  
sim\_hmm, 8, 9  
sim\_hmm\_paras, 8, 10  
sim\_lhmm, 8, 11  
sim\_lhmm\_paras, 8, 12  
statmod, 7